



Product Code PSEURO-15

Description

15A 12v EURO 5 & EURO 6 engine leisure battery charging system. Stop start Systems Used for Smart Alternator charging systems & Vehicles with Regenerative Braking, (Mercedes Benz Blue Efficiency Vehicles, VW Blue Motion Vehicles, Ford ECONetic vehicles, Vauxhall ecoFlex vehicles to name a few).



Specification

OUTPUT LOAD CURRENT: 15A Max
INPUT VOLTAGE: 12V nominal (9-32v)
NO LOAD INPUT CURRENT: 2mA @ 12v input
EMC: E11 Approved CE approved
PROTECTION: Automatic overload and over temperature protection with fully automatic reset
OUTPUT VOLTAGE: 12V
ISOLATION: Non-isolated
OPERATING TEMPERATURE: Maximum 70oC. Minimum -30oC
SIZE AND WEIGHT: Length: 150mm, Height: 44mm, Width: 84mm, 550g

Suitable for: Most Lead Acid, Gel, AGM batteries
Fan less cooling for zero noise

Approvals E11 Approval-Immunity requirements UNECE regulation 1 0 issue 4 Which covers all aspects of STANDARDS: EN50489:201 0 & CE Approval-Immunity to requirements of

12V INPUT	POSITIVE	RED
12V OUTPUT	POSITIVE	WHITE
COMMON	NEGATIVE	BLACK
CONTROL	POSITIVE	YELLOW

Box Contents

Charger, 500mm flying leads of thin wall auto cable, Manual