Parksafe - Product Specification Sheet

Wireless Forklift Camera

Our new Forklift Camera features not only FHD quality picture resolution but also an inbuilt battery for convenience of fitting.
The Battery charges in just over two hours and will provide 10 hours of runtime.
The Ultra Strong magnet will hold the Camera securely but it also has two fixing points for fixing with countersink screws.

PSFLTCAM.1

Key Specification:

Power Supply: 12V
TV System: PAL/NTSC
Sensor:: 1/2.9 CMOS
TV Line: 720P
Effective Pixels: 1280H × 720V
IP Grade: IP68
Sync. System: Internal
Minimum Illumination: 0.1Lux
Power consumption: 1.85W

Additional Specification:

LED Qty: 2PCS
Output Signal Amplitude: 1.0VP-P.75 ohm
White Balance, Shutter, BLC: Auto
Electronic Shutter: 1/50/60-1/10000 seconds
Gamma: 0.45
Built-in power supply: 3.7V/5000mAh
Charge: Supports 5V@3A/9V@2A/12V@1.5A voltage input, with a maximum charging power of 18W.
Fast charging protocol: QC2.0/QC3.0/PD2.0/PD3.0/FCP/AFC
Working hours at normal temperature: 10H
Charging time: 2.3H
Image delay: ＜200ms
Lens focal length: 6mm
Lens angle: Horizontal 52°/vertical 30°/diagonal 55°
Open air transmission distance: 110m

Working temperature: -20℃~+60℃，RH 95% MAX
Storage temperature: -20℃~+60℃，RH 95% MAX

Date Created:
11/01/2024

Last modified:
11/01/2024

Specification Sheet Number:
JAY10010242

Version:
V1.0

Box Dimensions (WxDxH):
230mm x 140mm x 70mm

Approvals & Certifications:

CE

Box Contents:

Camera; Charging Lead; UK Plug; Instructions.